

Tork Universal Aftørningspapir 310 Gul Rulle



Artikel: 127107

System: W1 - Aftørningspapir væg-/gulv-/standardsystem

Lag: 1

Farve: Gul

Tryk:

Prægning:

Rullebredde: 33 cm

Rullelængde: 1190 m

Rullediameter: 38 cm

Indvendig kerner diameter: 7.1 cm

Produktspecifikation

- Allroundaftørningspapir til lettere opgaver og steder med stort forbrug
- Økonomisk
- Robust og vådstærkt

Forsendelsesdata

Forbrugerenhed:

EAN: 7322540069723

Stk.: 1

Højde: 330 mm

Bredde: 380 mm

Længde: 380 mm

Volumen: 47.7 dm³

Nettovægt: 10014 g

Bruttovægt: 10100 g

Transportenhed:

EAN: 7322540069723

Stk.: 1

Forbrugerenheder: 1

Materiale: Plastic

Højde: 330 mm

Bredde: 380 mm

Længde: 380 mm

Volumen: 47.7 dm³

Nettovægt: 10.01 kg

Bruttovægt: 10.14 kg

Miljø

Content

Recycled fibres, Chemicals

Material

Recycled fibres Recovered paper can be produced both from collected newsprint, magazines and office waste. The paper is washed with water and treated with chemicals under high temperature and then filtered. Different fibres demand different processes and this determines the end product properties, and makes the fibre type (recovered or virgin) less important. The environmental benefits and economic feasibility of recovered paper as a raw material source depend on its

availability, transport distance and the quality of the collected material.

Bleaching of fibres

Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety. There are different methods used today for bleaching ECF (elementary chlorine free) where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view. The used functional chemicals are: Wet strength agent Dry strength agent If coloured = Dye Fixing agents Fluorescent whitening agent Glue Softeners The process chemicals are: Antipitch Protection agent Yankee coating Defoamer Dispersing agents and surfactants pH and charge control Retention aids Broke treatment chemicals Drainage aid

Product safety

The product fulfils the legislative requirements for food safety = Isega. Packaging Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label Approved and labeled according to Swan. License no. 305003.

Date of issue 2007-08-27

Revision date 2009-11-02

Production

This product is produced in Lilla Edet mill, Sweden, certified according to ISO 9001, ISO 1400.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.