

Tork Advanced Aftøringspapir 415 Combi



Artikel: 131135

System: W2 - Aftøringspapir kombirullesystem,
W1 - Aftøringspapir væg-/gulv-/standardsystem

Lag: 1

Farve: Hvid

Tryk:

Prægning:

Rullebredde: 24.5 cm

Rullelængde: 460 m

Antal ark: 1150

Arklængde: 40 cm

Rullediameter: 26.5 cm

Indvendig kerner diameter: 7.1 cm

Produktspecifikation

- God sugsevne og stor styrke.
- Velegnet til områder med stort forbrug
- Fungerer lige godt med opløsningsmidler som med vand

Forsendelsesdata

Forbrugerenhed:

EAN: 7310791200897

Stk.: 1

Højde: 245 mm

Bredde: 265 mm

Længde: 265 mm

Volumen: 17.2 dm³

Nettovægt: 2930 g

Bruttovægt: 2970 g

Transportenhed:

EAN: 7310791200903

Stk.: 2

Forbrugerenheder: 2

Materiale: Plastic

Højde: 245 mm

Bredde: 265 mm

Længde: 530 mm

Volumen: 34.4 dm³

Nettovægt: 5.86 kg

Bruttovægt: 6.00 kg

Miljø

Content

Virgin pulp, Recycled fibres, Chemicals

Material

Virgin fibres and recovered paper

In the tissue process both virgin fibres and recovered paper are being used. In the process it is a matter of finding an efficient solution where both virgin fibres and recovered paper play a role.

Different fibres demand different processes and this determines the end product properties, and makes the fibre type (recovered or virgin) less important. The environmental benefits and economic feasibility of recovered paper as a raw material source depend on its availability,

transport distance and the quality of the collected material.

Bleaching of fibres

Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety. There are different methods used today for bleaching ECF (elementary chlorine free) where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view. The used functional chemicals are: Wet strength agent Dry strength agent If coloured = Dye Fixing agents If white Fluorescent whitening agent If needed Glue Softeners The process chemicals are: Antipitch Protection agent Yankee coating Defoamer Dispersing agents and surfactants pH and charge control Retention aids Broke treatment chemicals Drainage aid

Product safety

The product fulfils the legislative requirements for food safety = Isega. Packaging Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label = Ecolabel. This product is approved for Swan label, licence 305 003.

Date of issue 2007-08-28

Revision date 2009-11-02

Production

This product is produced in Lilla Edet mill, Sweden, certified according to ISO 9001, ISO 14001.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.